

CLAIMS

WHAT IS CLAIMED:

suba
5

10
15
20
25

1. A method, comprising:
defining a process task;
performing a process simulation function to produce simulation data corresponding to
said process task; and
interfacing said simulation data with a process control environment for controlling a
manufacturing process of a semiconductor device;
2. The method described in claim 1, further comprising performing a
manufacturing process of the semiconductor device based upon said interfacing of said
simulation data with said process control environment.
3. The method described in claim 2, wherein performing manufacturing process
of said semiconductor device further comprises processing a semiconductor wafer.
4. The method described in claim 3, wherein defining a process task further
comprises defining a photolithography process task.
5. The method described in claim 3, wherein defining a process task further
comprises defining an etch process task.
6. The method described in claim 3, wherein defining a process task further
comprises defining a chemical-mechanical polishing process task.

7. The method described in claim 3, wherein defining a process task further comprises defining an implant process task.

8. The method described in claim 3, wherein defining a process task further
5 comprises defining a diffusion process task.

9. The method described in claim 3, wherein performing a process simulation function further comprises:

preparing at least one processing model for simulation;

executing a simulation using said processing model to generate a simulation result;

determining whether said simulation result is within a predetermined specification;

and

applying said simulation result into at least one manufacturing parameter in response

to a determination that said simulation result is within said predetermined specification.

10. The method described in claim 9, further comprising modifying said model in response to a determination that said simulation result is not within said predetermined specification.

11. The method described in claim 9, wherein preparing at least one processing model for simulation further comprises:

defining at least one processing model;

validating said defined model;

acquiring data for operation of said defined model; and

populating said defined model with said acquired model.

12. The method described in claim 11, wherein defining at least one processing
model further comprises defining at least one of a device physics model, a process model,
5 and an equipment model.

13. The method described in claim 11, wherein validating said defined model
further comprises integrating a plurality of defined models into a simulation environment.

10 14. The method described in claim 9, wherein executing said simulation using said
processing model to generate a simulation result further comprises:
modulating at least one variability in said processing model;
executing a model behavior based upon said variability;
determining at least one component of variation based upon said execution of the
15 model behavior; and
determining whether component of variation is within a predetermined specification.

15 15. The method described in claim 14, wherein modulating at least one variability
in said processing model further comprises modulating a temperature component.

20 16. The method described in claim 14, further comprising performing a predictive
state analysis in response to said execution of said model behavior.

25 17. The method described in claim 14, further comprising performing a sensitivity
analysis in response to said execution of said model behavior.

18. The method described in claim 9, wherein applying said simulation result into at least one manufacturing parameter further comprises modifying at least one manufacturing control parameter based upon said simulation result.

5

19. A system, comprising:

a computer system;

a manufacturing model coupled with said computer system, said manufacturing model

being capable of generating and modifying at least one control input parameter

signal;

a machine interface coupled with said manufacturing model, said machine interface

being capable of receiving process recipes from said manufacturing model;

a processing tool capable of processing semiconductor wafers and coupled with said

machine interface, said first processing tool being capable of receiving at least

one control input parameter signal from said machine interface;

a metrology tool coupled with said first processing tool and said second processing

tool, said metrology tool being capable of acquiring metrology data;

a metrology data analysis unit coupled with said metrology, said metrology data

analysis unit being capable of organizing said acquired metrology data; and

a simulation environment coupled to said metrology data analysis unit and said

computer system, said simulation environment capable of producing

simulation data for controlling manufacturing of semiconductor wafers.

10
15
20

20. The system of claim 19, wherein said computer system is capable of generating modification data for modifying at least one control input parameter in response to a said simulation data.

5 21. The system of claim 20, wherein said manufacturing model is capable of modifying said control input parameter in response to said modification data.

22. The system of claim 19, wherein said simulation environment comprises:

a simulator, said simulator being capable of simulating a manufacturing process of a semiconductor wafer;

a device physics model coupled to said simulator, said device physics model being capable of emulating semiconductor wafer manufacturing characteristics;

a process model coupled to said simulator, said process model being capable of emulating a semiconductor wafer manufacturing process;

an equipment model coupled to said simulator, said equipment model being capable of emulating a semiconductor wafer manufacturing process tool; and

a process control interface coupled to said simulator, said process control interface being capable of facilitating communication between said simulation environment and a process control environment.

20 23. An apparatus, comprising:

means for defining a process task;

means for performing a process simulation function to produce simulation data corresponding to said process task; and

means for interfacing said simulation data with a process control environment for
controlling a manufacturing process of a semiconductor device;

24. A computer readable program storage device encoded with instructions that,
5 when executed by a computer, performs a method, comprising:

defining a process task;

performing a process simulation function to produce simulation data corresponding to
said process task; and

interfacing said simulation data with a process control environment for controlling a
manufacturing process of a semiconductor device;

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500

25. The computer readable program storage device encoded with instructions that,
when executed by a computer, performs the method described in claim 24, further comprising
performing a manufacturing process of the semiconductor device based upon said interfacing
of said simulation data with said process control environment.

26. The computer readable program storage device encoded with instructions that,
when executed by a computer, performs the computer readable program storage device
encoded with instructions that, when executed by a computer, performs the method described
20 in claim 25, wherein performing manufacturing process of said semiconductor device further
comprises processing a semiconductor wafer.

27. The computer readable program storage device encoded with instructions that,
when executed by a computer, performs the method described in claim 26, wherein defining a
25 process task comprises defining a photolithography process task.

28. The computer readable program storage device encoded with instructions that, when executed by a computer, performs the method described in claim 26, wherein defining a process task comprises defining an etch process task.

5

29. The computer readable program storage device encoded with instructions that, when executed by a computer, performs the method described in claim 26, wherein defining a process task comprises defining a chemical-mechanical polishing process task.

30. The computer readable program storage device encoded with instructions that, when executed by a computer, performs the method described in claim 26, wherein defining a process task further comprises defining an implant process task.

31. The computer readable program storage device encoded with instructions that, when executed by a computer, performs the method described in claim 26, wherein defining a process task further comprises defining a diffusion polishing process task.

32. The computer readable program storage device encoded with instructions that, when executed by a computer, performs the method described in claim 26, wherein performing a process simulation function further comprises:

preparing at least one processing model for simulation;

executing a simulation using said processing model to generate a simulation result;

determining whether said simulation result is within a predetermined specification;

and

applying said simulation result into at least one manufacturing parameter in response to a determination that said simulation result is within said predetermined specification.

5 33. The computer readable program storage device encoded with instructions that, when executed by a computer, performs the method described in claim 32, further comprising modifying said model in response to a determination that said simulation result is not within said predetermined specification.

10 34. The computer readable program storage device encoded with instructions that, when executed by a computer, performs the method described in claim 32, wherein preparing at least one processing model for simulation further comprises:
15 defining at least one processing model;
 validating said defined model;
 acquiring data for operation of said defined model; and
 populating said defined model with said acquired model.

20 35. The computer readable program storage device encoded with instructions that, when executed by a computer, performs the method described in claim 34, wherein defining at least one processing model comprises defining at least one of a device physics model, a process model, and an equipment model.

36. The computer readable program storage device encoded with instructions that, when executed by a computer, performs the method described in claim 34, wherein validating

said defined model further comprises integrating a plurality of defined models into a simulation environment.

37. The computer readable program storage device encoded with instructions that,
5 when executed by a computer, performs the method described in claim 32, wherein executing said simulation using said processing model to generate a simulation result further comprises:

modulating at least one variability in said processing model;

executing a model behavior based upon said variability;

determining at least one component of variation based upon said execution of the

10 model behavior; and

determining whether component of variation is within a predetermined specification.

10
15
20
25
30
35
40
45
50
55
60
65
70
75
80
85
90
95
100
105
110
115
120
125
130
135
140
145
150
155
160
165
170
175
180
185
190
195
200
205
210
215
220
225
230
235
240
245
250
255
260
265
270
275
280
285
290
295
300
305
310
315
320
325
330
335
340
345
350
355
360
365
370
375
380
385
390
395
400
405
410
415
420
425
430
435
440
445
450
455
460
465
470
475
480
485
490
495
500

38. The computer readable program storage device encoded with instructions that,
when executed by a computer, performs the method described in claim 37, wherein
15 modulating at least one variability in said processing model further comprises modulating a temperature component.

39. The computer readable program storage device encoded with instructions that,
when executed by a computer, performs the method described in claim 37, further comprising
20 performing a predictive state analysis in response to said execution of said model behavior.

40. The computer readable program storage device encoded with instructions that,
when executed by a computer, performs the method described in claim 37, further comprising
performing a sensitivity analysis in response to said execution of said model behavior

25

41. The computer readable program storage device encoded with instructions that, when executed by a computer, performs the method described in claim 32, wherein applying said simulation result into at least one manufacturing parameter further comprises modifying at least one manufacturing control parameter based upon said simulation result.

5

mutatis
~~42. A method, comprising:~~

~~defining a process task;~~

~~performing a process simulation function to produce simulation data corresponding to~~

~~said process task, said process simulation function comprising:~~

~~preparing at least one processing model for simulation;~~

~~executing a simulation using said processing model to generate a
simulation result;~~

~~determining whether said simulation result is within a predetermined
specification; and~~

~~applying said simulation result into at least one manufacturing
parameter in response to a determination that said simulation
result is within said predetermined specification.~~

and

interfacing said simulation data with a process control environment for controlling a

manufacturing process of a semiconductor device;

43. The method described in claim 38, further comprising modifying said model in response to a determination that said simulation result is not within said predetermined specification.

25

44. The method described in claim 38, wherein preparing at least one processing model for simulation further comprises:

defining at least one processing model;

validating said defined model;

5 acquiring data for operation of said defined model; and

populating said defined model with said acquired model.

45. The method described in claim 40, wherein defining at least one processing model further comprises defining at least one of a device physics model, a process model, and an equipment model.

46. The method described in claim 40, wherein validating said defined model further comprises integrating a plurality of defined models into a simulation environment.

47. The method described in claim 38, wherein executing said simulation using said processing model to generate a simulation result further comprises:

modulating at least one variability in said processing model;

executing a model behavior based upon said variability;

determining at least one component of variation based upon said execution of the

20 model behavior; and

determining whether component of variation is within a predetermined specification.

48. A method, comprising:

defining a graph relating to a desired results of a processed semiconductor wafer;

25 defining a graph relating to a predicted results of said processed semiconductor wafer;

comparing said graph relating to said desired results to said graph relating to said predicted results to determine a difference between said graphs; and adjusting at least one control input parameter for a manufacturing process based upon said difference between said graphs.

5

49. The method described in claim 48, wherein defining said graph relating to the desired results of said processed semiconductor wafer further comprises defining said graph relating to at least one electrical parameter of a semiconductor wafer.

10

50. The method described in claim 49, wherein defining said graph relating to at least one electrical parameter of a semiconductor wafer further comprises defining said graph relating to a speed of operation of a circuit formed on said semiconductor wafer.

15

51. The method described in claim 48, wherein defining said graph relating to the predicted results of said processed semiconductor wafer further comprises defining said graph relating to at least one electrical parameter of a semiconductor wafer.

20

52. The method described in claim 51, wherein defining said graph relating to at least one electrical parameter of a semiconductor wafer further comprises defining said graph relating to a speed of operation of a circuit formed on said semiconductor wafer.

25

53. The method described in claim 48, further comprising:
defining a graph relating to an actual result of said processed semiconductor wafer;
comparing said graph relating to said actual result to said graph relating to said desired results and to said graph relating to said predicted results;

adjusting at least one control input parameter for a manufacturing process based upon
said comparison.

54. The method described in claim 53, wherein defining said graph relating to the
5 actual results of said processed semiconductor wafer further comprises defining said graph
relating to at least one electrical parameter of a semiconductor wafer.

55. The method described in claim 55, wherein defining said graph relating to at
least one electrical parameter of a semiconductor wafer further comprises defining said graph
10 relating to a speed of operation of a circuit formed on said semiconductor wafer.